



ESBOvalve **M 202**

The M 202 is a ball valve with two-piece body, threaded ends and a blow-off proof stem design. It is free of silicone and features an ISO 5211 top flange.



ESB0valve M 202

The ESB0valve M 202 is a ball valve with two-piece body and threaded ends. It features an ISO 5211 top flange for fitting actuators or similar accessories, is silicone-free and has a blow-off proof stem design.



Technical data

Through-bore	1/4" – 2"
Overall length	DIN 3202 M3
Pressure class	PN 63 (1/4" – 2")
Enclosure, end cap, ball	1.4408 (316)
Spindle	1.4401 (316)
Thrust washer, spring washer, nut	1.4401 (316)
O-ring (DVGW-GAS, DIN 3535 Part 3)	Viton
Ball seal, sliding ring, packing box, etc.	PTFE, TFM 1600 or RTFE
Handle	1.4301 (304), plastic covering
Threaded ends	DIN EN 10226-1 (previously DIN 2999-1), NPT or BS
Actuators	Hand lever, electrical or pneumatic actuation (ISO 5211)

Dimensions

Size	Bore	ØD	L	H	I	F
1/4"	DN 8	11,6	50	33,2	9	F03-F04
3/8"	DN 10	12,7	60	33,2	9	F03-F04
1/2"	DN 15	15	75	35	9	F03-F04
3/4"	DN 20	20	80	44,1	11	F04-F05
1"	DN 25	25	90	44,5	11	F04-F05
1¼"	DN 32	31,8	110	49,4	11	F04-F05
1½"	DN 40	38	120	55	11	F04-F05
2"	DN 50	50,8	140	66,5	14	F05-F07

ØD: Bore diameter of the ball

L: Face-to-face length of the ball valve

H: Height from boresight to the top edge of the ISO 5211 top flange

I: Size of the square-end for fitting actuators

F: Hole pattern of the ISO 5211 top flange

All dimensions in millimeters (mm)

Other versions

The M 202 is also available in version M 202 Gas with gas approval.



ESBO GmbH

Erbsengasse 28
D-69469 Weinheim
Deutschland

Telefon +49 6201 63081
Telefax +49 6201 17917

info@esbo.de
sales.bulk@esbo.de
www.esbo.de